

Keyspan Mini DisplayPort to Active VGA Adapter, Video Converter (M/F), White, 6-in. (15.24 cm)

MODEL NUMBER: P137-06N-VGA







Connect a VGA monitor to a Mac or PC with a Mini Displayport output

Features

- Connect a VGA monitor to a Mac or PC with a Mini Displayport output
- Compatible with Thunderbolt 1 and 2 ports on Mac computers
- Plug-and-play convenience—no drivers or software needed
- Supports computer video resolutions up to 1920 x 1200, and HD resolutions up to 1080p
- Ideal for use with graphics cards, such as AMD Eyefinity, that do not output Dual Mode (DP++) signals
- Converts both Single-Mode and Dual Mode (DP++) Displayport output

Highlights

- Connect a VGA monitor to a Mac or PC with a Mini Displayport output
- Compatible with Thunderbolt 1 and 2 ports on Mac computers
- Plug-and-play convenience—no drivers or software needed
- Supports computer video resolutions up to 1920 x 1200, and HD resolutions up to 1080p
- Ideal for use with graphics cards, such as AMD Eyefinity, that do not output Dual Mode (DP++) signals
- Converts both Single-Mode and Dual Mode (DP++) Displayport output

System Requirements

- Mac or PC with a Mini
 Displayport port; Compatible
 with Thunderbolt 1 and 2 ports
 on Mac computers
- Monitor with a VGA port
- Not for use with MST Hubs. For compatibility with MST Hubs, use a Displayport 1.2 compliant product such as P137-06N-VGA-V2

Package Includes

 Mini-DisplayPort to Active VGA Adapter

Specifications

| OVERVIEW | | |
|--------------------|-----------------------|--|
| OVERVIEW | | |
| UPC Code | 037332158901 | |
| Technology | VGA/SVGA; DisplayPort | |
| | | |
| PHYSICAL | | |
| Color | White | |
| Cable Length (ft.) | 0.5 | |
| Cable Length (m) | 0.15 | |
| Cable Length (in.) | 6 | |
| Cable Length (cm) | 15.24 | |





| Shipping Dimensions (hwd / cm) | 22.86 x 17.78 x 0.03 |
|--|-------------------------|
| Shipping Dimensions (hwd / in.) | 9.00 x 7.00 x 0.01 |
| Shipping Weight (kg) | 0.02 |
| Shipping Weight (lbs.) | 0.05 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 0 C ~ 70 C |
| Storage Temperature Range | 10 C ~ 80 C |
| Operating Humidity Range | 10% ~ 85% RH |
| Storage Humidity Range | 5% ~ 90% RH |
| CONNECTIONS | |
| Side A - Connector 1 | MINI DISPLAYPORT (MALE) |
| Side B - Connector 1 | HD15 (FEMALE) |
| STANDARDS & COMPLIANCE | |
| Product Compliance | RoHS |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies